PHYSICAL SCIENCES INC.

VG06-206

Plasma Sheathing Control Using Boundary Layer Stabilization and Additives

Hartmut H. Legner, John F. Cronin and W. Terry Rawlins
Physical Sciences, Inc., Andover, MA
Substitute Speaker: Dr. Robert F. Weiss, Physical Sciences Inc.

Paper Presented at
AFOSR Workshop on Communications Through Plasma
During Hypersonic Flight

29 August 2006, Boston, MA

Acknowledgement of Support and Disclaimer
This material is based upon work supported by the United States Air Force under Contract Number FA8718-05-C-0054. Any opinions, findings and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the United States Air Force.

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE	2. REPORT TYPE	3. DATES COVERED
29 AUG 2006		**00-00-2006 to 00-00-2006**

4. TITLE AND SUBTITLE	5a. CONTRACT NUMBER
Plasma Sheathing Control Using Boundary Layer Stabilization and Additives	5b. GRANT NUMBER
	5c. PROGRAM ELEMENT NUMBER
6. AUTHOR(S)	5d. PROJECT NUMBER
	5e. TASK NUMBER
	5f. WORK UNIT NUMBER
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) **Physical Sciences Inc,20 New England Business Center,Andover,MA,01810**	8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)	10. SPONSOR/MONITOR'S ACRONYM(S)
	11. SPONSOR/MONITOR'S REPORT NUMBER(S)

12. DISTRIBUTION/AVAILABILITY STATEMENT
Approved for public release; distribution unlimited

13. SUPPLEMENTARY NOTES

14. ABSTRACT

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT **unclassified**	b. ABSTRACT **unclassified**	c. THIS PAGE **unclassified**	**Same as Report (SAR)**	**20**	

Acknowledgment and Note

- **This Phase I SBIR effort was sponsored by two AFRL organizations: SNHE and VAAC, with additional interest from a third organization: VSBXT**

- **The technical monitor is Dr. James Ernstmeyer of AFRL/SNHE at Hanscom AFB, MA**

- **<u>Special note</u>: This presentation provides a general overview of potential sheathing solutions. Specific results and designs have SBIR rights and ITAR restrictions. The detailed report can be obtained from Dr. Ernstmeyer.**

Outline

- **Plasma sheathing control objectives**
- **Three techniques**
  - Boundary layer stabilization by extreme cooling
  - Liquid injection into boundary layer flow
  - Electrophilic material in heat shield material
- **Application to hypersonic vehicles**
- **Summary**

Plasma Sheathing Control Objectives

VG06-206-3



- **Control sheathing via temperature and chemistry**
- **Reduce electron density, n_e**
- **Reduce boundary layer thickness, δ**

PSI
PHYSICAL SCIENCES INC.

Plasma Sheath Attenuation Reduction
BRV, 50 kft, n_e = 1.8 x 10^{12}/cm^3, 0.130 atm, ν_c = 1.3x10^{10} S^{-1}

VG06-206-4

Boundary Layer Thickness Reduction



G-9836a

PSI
PHYSICAL SCIENCES INC.

Plasma Sheath Attenuation Reduction
BRV, 50 kft, Delta = 1.4 cm, 0.130 atm, ν_c = 1.3x10^{10} S^{-1}

VG06-206-5

Electron Density Reduction



H-9940

PHYSICAL SCIENCES INC.

Extreme Surface Cooling Using Hydride Materials

- **Extreme cooling stabilizes hypersonic boundary layer**
  - Secondary mode unstable at high edge mach number
  - Remain below $M_{e_{2nd\ mode}}$ for laminar flow
- **Hydride cooling works over a large range of heating conditions**
  - Amount of hydride (material thickness) controls “cool time”
- **Hydrogen gas released during low-temperature ablation process**
  - 15-20 kJ/gm H_2 , heat of desorption (and adsorption)

Hydride cooling works over wide range of trans-atmospheric flight conditions

Hydride Cooling for Typical Surface Heating Flux 50 W/cm²

VG06-206-7



Computations performed using PSI's validated thermal response code

PHYSICAL SCIENCES INC.

Cooling Stabilization Boundary for Trans-atmospheric Trajectory Points

VG06-206-8



H-7446a

PHYSICAL SCIENCES INC.

Liquid Injection

- **NASA RAM C-III Flight Experiment 1973**
  - $n_e(cm^{-3})$ at boundary layer standoff distance 4 cm, 71-72 km altitude
    - No injection: $3.9x10^{10}$
    - Water: $4.8x10^{9}$
    - Freon-3: $3.8x10^{8}$
  - Blunt vehicle, Teflon frustum, 5000 ppm alkali impurities, pulsed injection

- **Employed Non-equilibrum Boundary Layer (NEBL) code to compute effects of injectant on downstream electron density**
  - Same trans-atmospheric flight conditions as hydride
  - Instantaneous vaporization
  - 50 ppm alkali in carbon phenolic heatshield
  - Wall cooling effects

Water injection showed insignificant effects, but Freon-3 resulted in orders of magnitude n_e reduction depending on boundary layer cooling

Freon Injection Cases

VG06-206-10

$n_e(cm^{-3})$



T(ºk)



PHYSICAL SCIENCES INC.

Heatshield Electrophilic Scavenging Computations

VG06-206-11

- **Electrophilic particles take up electrons efficiently by the reaction**

$$P + e^- \underset{k_d}{\overset{k_a}{\bullet}} P^-$$

- **Applied heterogeneous chemistry model, Caledonia (1986)**
  - Electrophilic specie concentration (ppm)
  - Particle size (Å)
  - Work function (eV)
  - Temperature (K)

PSI
PHYSICAL SCIENCES INC.

Electron Density Reduction

VG06-206-12



Large potential sheathing reduction using low concentration of electrophilic material

PSI
PHYSICAL SCIENCES INC.

Vehicle Application

VG06-206-13

Requirements	Plasma Sheathing Control Techniques		
	Boundary Layer Transition Control	**Additive Injection**	**Incorporation of Electrophilic Species**
Missions			
Weapon	One-time control	Multiple control applications	Continuous
Surveillance	Multiple applications	Multiple control applications	Continuous
Altitude History			
Velocity Time	Velocity dependent 5-20 s	Some velocity dependence 5-20 s, pulse	Some velocity dependence Continuous or pulsed
Configuration			
Waverider	Compatible	Compatible	Compatible, distributed in heatshield or injected
Bi-conic	Compatible	Compatible	Compatible, distributed in heatshield or injected
Design			
• Volume Impact	Small	Modest	Very small
• Weight Impact	Small	Modest	Very small
• Power Impact	Very small	Small	None, small if injected

PSI
PHYSICAL SCIENCES INC.

Summary

- **Three general techniques to control plasma sheathing have been identified.**
- **All three schemes are potentially viable for application to hypersonic cruise vehicles.**
- **Experimental validation and multi-phase modeling simulations are needed to pursue this promising technology further.**

Backup Charts

Metallic Hydrides

VG06-206-16

- **Transition metal hydrides**
  - $A_xB_{l-X}H_y$ type compounds
  - decompose rapidly and endothermically to produce H_2

$$A_xB_{l-x}\,H_y \rightarrow A_xB_{l-x} + y/2\ H_2$$

Heats of Desorption (and Adsorption)

$LaNi_5H_6 = LaNi_5 + 3\ H_2$ $\quad \Delta H = 15.1$ kJ/gm H_2

and

$(V_{0.89}Ti_{0.11})_{0.95}Fe_{0.05}H_x$, =

$(V_{0.89}Ti_{0.11})_{0.95}Fe_{0.05}H_{x-1} + 1/2H_2$ $\quad \Delta H = 21.5$ kJ/gm H_2

- High energy, low temperature ablators

H_2 Flow as a Function of Heating Rate for $LaNi_5H_6$



H_2 Pressure Above $LaNi_5H_6$ (—) and $(V_{0.89}Ti_{0.11})_{0.95}Fe_{0.05}H_x$(•–•)



PHYSICAL SCIENCES INC.

Boundary Layer Models

- **Non-Equilibrium BL (NEBL) Code**
  - implicit, fully-coupled model
  - unique chemistry models
- **TURBL**
  - 8 equation turbulence model
  - temperature fluctuations mirror plasma behavior
- **REACH (developed by SAIC)**
  - 3D BL Code

NEBL Methodology

VG06-206-17



NEBL Calculation



Teflon
RMV-340
131 kft

REACH Simulation



PHYSICAL SCIENCES INC.

Water Injection Cases

$n_e(cm^{-3})$



T(°k)



PHYSICAL SCIENCES INC.

Freon Injection
Synergistic Effects: Hydride Cooling and Injection

VG06-206-19

$n_e(cm^{-3})$



T(°k)



PHYSICAL SCIENCES INC.